

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

η_e [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	η _e [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CBPC-1445-4T IE3	A	Static	VSD not necessary	1.01	58.8	69.1	1.034	4027	543	1464
CBPC-1650-4T-2 IE3	A	Static	VSD not necessary	1.01	65.7	73.7	1.702	6705	600	1441
CBPC-1650-4T-3 IE3	A	Static	VSD not necessary	1.01	63.4	70.3	2.192	7825	639	1444
CBPC-1556-4T IE3	A	Static	VSD not necessary	1.01	59.4	65.6	2.558	8099	675	1455
CBPC-1856-4T-4 IE3	A	Static	VSD not necessary	1.01	60.5	65.7	3.147	9555	717	1445
CBPC-1856-4T-5.5 IE3	A	Static	VSD not necessary	1.01	61.1	65.8	3.612	9478	838	1460