

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP)

|            |                      |
|------------|----------------------|
| <b>MC</b>  | Measurement category |
| <b>EC</b>  | Efficiency category  |
| <b>VSD</b> | Variable Speed Drive |
| <b>SR</b>  | Specific ratio       |

|                          |                                  |
|--------------------------|----------------------------------|
| <b>[m<sup>3</sup>/h]</b> | Flow rate                        |
| <b>[Pa]</b>              | Static pressure / Total pressure |
| <b>[RPM]</b>             | Speed                            |

|               |                  |
|---------------|------------------|
| <b>ηe [%]</b> | Efficiency       |
| <b>N</b>      | Efficiency grade |
| <b>[kW]</b>   | Input power      |

| Model             | MC | EC | VSD | SR | ηe[%] | N | [kW] | [m <sup>3</sup> /h] | [Pa] | [RPM]                    |
|-------------------|----|----|-----|----|-------|---|------|---------------------|------|--------------------------|
| HPX-35-2T-0.75    |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-35-4T-0.33    |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-45-4T-0.33    |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-45-4T-0.50    |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-50-4T-0.75    |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-50-4T-1 IE3   |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-56-4T-0.75    |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-56-4T-1 IE3   |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-56-4T-1.5 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-63-4T-1.5 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-63-4T-2 IE3   |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-71-4T-1.5 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-71-4T-2 IE3   |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-71-4T-3 IE3   |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-80-4T-4 IE3   |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-80-4T-5.5 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-90-4T-5.5 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-90-4T-7.5 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-100-4T-10 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |
| HPX-100-4T-15 IE3 |    |    |     |    |       |   |      |                     |      | Exclude. Gas Temp> 100°C |