

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

η_e [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	η _e [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
HTM/ATEX-35-2T/2G Ex db										ErP: Exclude. ATEX
HTM/ATEX-35-4T/2G Ex db										ErP: Exclude. ATEX
HTM/ATEX-40-4T/2G Ex db										ErP: Exclude. ATEX
HTM/ATEX-45-4T/2G Ex db										ErP: Exclude. ATEX
HTM/ATEX-56-4T/2G Ex db										ErP: Exclude. ATEX
HTM/ATEX-63-4T/2G Ex db										ErP: Exclude. ATEX
HTM/ATEX-35-2T/2G Ex eb										ErP: Exclude. ATEX
HTM/ATEX-35-4T/2G Ex eb										ErP: Exclude. ATEX
HTM/ATEX-40-4T/2G Ex eb										ErP: Exclude. ATEX
HTM/ATEX-45-4T/2G Ex eb										ErP: Exclude. ATEX
HTM/ATEX-56-4T/2G Ex eb										ErP: Exclude. ATEX
HTM/ATEX-63-4T/2G Ex eb										ErP: Exclude. ATEX