

ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

www.sodeca.com

- | | | | | |
|---------------|--|---|---|--------------------------|
| b) Model | f) Thermal efficiency of heat recovery (%) | j) Face velocity at design flow rate | n) Static efficiency of fans according to (EU) 327/2011 | q) Visual filter warning |
| c) Typology | g) Nominal flowrate | k) Nominal external pressure | o1) Max. internal leakage rate | r) LWA radiated |
| d) Drive type | h) Effective electric power input | l) Internal pressure drop of ventilation components | o2) Max. external leakage rate | |
| e) HRS type | i) SFPint | m) Internal pressure drop of non-ventilation components | p) Energy performance of the filters | |

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
				%	m ³ /s	kW	Wm ³ /s	m/s	Pa	Pa	Pa	%	%	%			dBA	
CJLINE/EC-1131-4M-0.33 IE5	NRVU / UVU	Variable speed	Not applicable		0.323	0.157	230	1.30	212			53.1	1.1		Not applicable	See manual	65	2018
CJLINE/EC-1235-4M-0.33 IE5	NRVU / UVU	Variable speed	Not applicable		0.472	0.222	230	1.60	262			54.3	1.1		Not applicable	See manual	72	2018
CJLINE/EC-1640-4M-0.75 IE5	NRVU / UVU	Variable speed	Not applicable		0.030	0.479	230	1.80	377			58.1	1.3		Not applicable	See manual	77	2018
CJLINE/EC-1845-4M-1.5 IE5	NRVU / UVU	Variable speed	Not applicable		1.020	0.584	230	2.00	494			51.6	1.3		Not applicable	See manual	81	2018
CJLINE/EC-1856-6M-1.5 IE5	NRVU / UVU	Variable speed	Not applicable		1.273	0.699	230	1.60	303			48.4	1.3		Not applicable	See manual	78	2018